

# MATERIAL SAFETY DATA SHEET Conform to Regulation (EC) No. 1272/2008 (CLP)

SECTION 1: Identification of the substance/mixture and	of the Company /Undertaking
1.1. Product name/	FSS PROFESSIONAL; FSS INDUSTRIAL
Trade name	FSS - FIRE SUPPRESSION SYSTEMS
1.2. Material uses	Fire suppressants
1.3. Details of the supplier of the safety data sheet	ESP International Srl
	Via IV Novembre 132
	29122 Piacenza (PC) – Italy
	Manufacturing Plant:
	Strada per Chieri, no. 109
	14019 Villanova d'Asti, AT – Italy
	Phone +39/0141-945628
	Fax +39/0141- 946671
	Email: info@fss-esp.com
	Website: <u>www.fss-esp.com</u>
1.4. Emergency telephone number	POC: Mr. Enzo Perna
	telephone +39 0141 - 945628
	e.perna@fss-esp.com

# **SECTION 2: Hazard Identification**

2.1. Classification of the substances or mixture

Index #	Component	CAS NUMBER	EC NUMBER	CLP Classification Regulation EEC no. 1272/2008	DSD Classification 67/548/EEC
//	Potassium Nitrate	7757-79-1	231-818-8	2.14/3 Ox. Sol.3 H272	O; Oxidizer
//	DCDA	461-58-5	207-312-8	11	//
	Organic resin	9003-35-4	500-005-2	//	//

Adverse physiochemical, human health and environmental effects: No other hazards

2.2. Label elements

Pictogram: GHS03



Hazard Class and Category: Oxidizing solid, hazard category 3 Signal Word: Warning Hazard Statement: H272: may intensify fire; oxidizer



	1/15D5 Date. 1/2/2010 Rev. 1/0 5
General Statements:	
P102 Keep out of the reach of children	
P103 Read label instructions before use	
Precautionary Statement Prevention:	
P210 Keep away from heat/sparks/open flames/hot surfaces. — Do not smoke.	
P221 Take any precaution and keep away from combustible material	
P243 Avoid electrostatic loads	
P250 Avoid crash and strike	
P273 Do not waste the product and/or the casing	
Precautionary Statement Response: Fluid Aerosol	
P302+P350+P313 In case of skin contact: may cause redness or irritation. Rinse cautiously with ru	unning water
If skin irritation occurs get medical advice/attention.	
P304+P340+P313 In case of inhalation: remove to fresh air and keep at rest in a position comforta	ble for
breathing. Get medical attention for any breathing difficulty.	
P305+P351+P313 In case of eye contact: may cause redness or irritation. Rinse cautiously with ru	unning water for
several minutes. If eye irritation persists get medical advice/attention.	
P314 Seek medical attention for further treatment, observation, and support if necessary.	
P370+P380 In the event of a fire, evacuate the area and inform emergency services.	
Ignition of FSS Fire Suppression Systems produces a fire suppression aerosol.	
P370+P378 Water may be used as an additional suppression agent, as well as powder extinguishe	er and/or
CO2 extinguisher.	
Precautionary Statement Disposal:	
P501 Disposal should be in accordance with applicable national, state and local environmental cor	ntrol
regulations.	
2.3. Other Hazards	
No other hazards	

No	other	hazards
110	ouror	nuzurus

SECTION 3: Composition, Information on Ingredients						
3.1. Identification	CAS#	EC #	CLP Classification Regulation EEC no. 1272/2008	DSD Classification 67/548/EEC	%	Comments
Potassium Nitrate	7757-79-1	231-818-8	GHS03 Wng 2.14/3 Ox. Sol.3 H272 EUH 210	O; Oxidizer	≥43	Components are blended and pressed into a highly stable, molded form. Molded composition is contained within a stainless steel housing.
DCDA	461-58-5	207-312-8	//	//	≥32	No environmental exposure
Organic resin	9003-35-4	500-005-2	//	//	≥25	
Extinguishing Charge: Composition of the extinguishing charge is contained within a sealed aluminu casing. Polymerized mixture of Organic and Inorganic Salts						



	MSDS Date: 1/2/2018 Rev. No 5	
Fluid Aerosol:	Particulates of Potassium Salts, Nitrogen and Water Vapor	
PBT	N/A	
vPvB	N/A	
3.2. Other denomination:	Portable Condensed aerosol fire extinguisher	
SECTION 4: First Aid Measures		
4.1. Description of first aid measures		
Body	Extinguishing charge: None. Contact is impossible when the flame inhibitor is assembled. Do not touch the tube of the dispenser during/after use. Medical attention is unnecessary.	
Skin Contact / Eye Contact	Fluid Aerosol: after contact, wash/flush immediately with running water. Medical attention is necessary in case of direct contact burns	
4.2. Most important symptoms and effects, both acute and delayed	No information available.	
4.3. Indication of any immediate medical attention and special treatment needed	Seek medical attention for further treatment, observation and support, if necessary.	
SECTION 5: FIRE-FIGHTING MEASURES		

41010040 0

5.1. Extinguishing media Suitable extinguishing media: Water. Carbon dioxide (CO2) CO2 or Dry chemical fire extinguishers. 5.2. Special hazards arising from the substance or Do not inhale combustion gases. mixture Flammability of the product Beginning of self-ignition phenomena over 300°C (over 572°F). Medical attention is unnecessary. In the event of a fire, evacuate the area and inform emergency services. Ignition of FSS - Fire Suppression Systems produces a fire suppression aerosol. No specific measures are required as the product itself is a fire fighting agent. Use 5.3 Advice for fire-fighters breathing apparatus if required

## **SECTION 6: Accidental Release Measures**

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

No particular action: the emission of the extinguishing charge when the fire suppressant is assembled is impossible, as it is inert material.

See protective measures under point 7 and 8.

6.3. Methods and material for containment and cleaning up

If the devices come out from packaging they can be safely recovered by hand and should be inspected for damage prior to repacking. Suspect or damaged articles should be labelled and consigned for correct disposal.



6.4. Reference to other sections See also section 8 and 13

### SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Normal attention in handling.

In case of unintentional activation of the fire suppressant, wait for the complete aerosol discharge and ventilate the area. Avoid the direct contact of the product with open flames.

7.2. Conditions for safe storage, including any incompatibilities

Store in an environment between -10°C and +50°C, <u>not exposed to sunlight</u>. Avoid: shock, electric currents, static discharge, excessive heat and extended periods of storage at temperature greater than 50°C exposure to sunlight. Packaging in cardboard boxes; do not pile the boxes higher than 2 mt

Medical attention is unnecessary.

7.3 Specific end use(s) None in particular

SECTION 8: Exposure Controls, Person	al Protection
8.1 Control parameters	Potassium nitrate - Index: N/A, CAS: 7757-79-1, EC No: 231-818-8
	DCDA - Index: N/A, CAS: 461-58-5, EC No: 207-312-8
	Organic Resin - Index: N/A, CAS: 9003-35-4, EC No: 500-005-2
	TLV TWA: N.A.
8.2 Exposure controls	
Respiratory protection	Ventilate area completely after discharge. Do not enter the area prior to
	complete venting of enclosures. Use filter mask as necessary during clean-up
Hand protection	Wear gloves if necessary
Eye protection	Safety glasses are advisable if necessary
Skin protection	N/A
Personal protection:	No individual protection.
·	Stick to the instructions legible on the product and inside each packaging box.
Occupational exposure limits:	No specific occupational exposure limit.
Environmental exposure controls:	No information available.

SECTION 9: Physical and Chemical Properties	
9.1. Information on basic physical and chemical pl	operties
Appearance and odor of aerosol:	Beige to white in color.
	Odorless.
Auto-ignition temperature:	about 350°C (about 662°F)
Solubility in water:	Slightly soluble
Appearance of device:	steel cylinder High up to 330 mm in length and of mm 33 diameter
Extinguishing charge physical state:	from 20°C solid to 0°C solid (from 62°F solid to 32°F)
Usability Temperature:	-140°F to +320°F
Granulometry:	From 2 to 4 microns
Steam:	None
Conductivity:	Non conductor
Fluid Aerosol physical state:	Gaseous



	MSDS Date: 1/2/2018 Rev. No 5
Exit temperature: high, saf	ety distance from supply source 1mt
9.2. Other informationConductivityNoncondElectrostatic DischargeNoneUsability Humidityup to 98CorrosivenessNoneThermal ShockNoneResidue after useNegligibl	

## **SECTION 10: Stability and Reactivity**

10.1 Reactivity.

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability.

The product is stable under normal storage and temperature conditions.

10.3 Possibility of hazardous reactions.

None identified. During use no dangerous decomposition products are produced.

10.4 Conditions to avoid.

No specific data

10.5 Incompatible materials

10.6 Hazardous decomposition products:

None

Note: These devices are extremely stable below 125°C. They should be protected from fire, sources of electrical power, shock and high temperatures.

## SECTION 11: Toxicological Information

 11.1. Information on toxicological effects

 Toxic by-products of combustion are extremely low.

 Main by-products are listed below with 15 minute TWA values for a concentration of 50gr/m3:

 Gas
 15 minute Time Weighted Average in parts per million

 CO (carbon monoxide)
 57 ppm

NOx (nitrogen dioxide) <5 ppm Aerosol (particulates) 8,5 mg/m3

General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. Teratogenicity : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Reproductive toxicity : No known significant effects or critical hazards. Developmental effects : No known significant effects or critical hazards. Fertility effects : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics Eye contact No specific data Skin contact No specific data. Ingestion No specific data. Delayed and immediate effects and also chronic effects from short and long term exposure: N/A



SECTION 12: Ecological Informatic	on	
12.1 Toxicity		
These devices present no ecological	hazards.	
12.1.1. The aerosol produced after	er ignition has the following characteristics:	
ODP Ozone Depletion Po	tential = 0	
GWP Global Warming Po	tential = 0	
ATL Atmospheric Life Tim	ne = negligible	
12.2. Persistence and degradability	No information available.	
12.3. Bio accumulative potential	No information available	
12.4. Mobility in soil	No information available	
12.5. Results of PBT and vPvB asses	ssment	
No PBT information available.		
No vPvB information available		
12.6. Other adverse effects	No information available.	

# **SECTION 13: Disposal Considerations**

13.1. Waste treatment methods Disposal should be in accordance with applicable national, state and local environmental control regulations.

SECTION 14: Transport Information	
14.1. UN Code Number ADR-RID-AND-IMDG-IATA	UN 3178
14.2. Name of UN ADR-RID-AND-IMDG-IATA	Flammable solid, inorganic, n.o.s.
14.3. Hazard Class ADR-RID-AND-IMDG-IATA	Classification 4.1
14.4 Packing Group ADR-RID-AND-IMDG IATA	III Passenger aircraft rail: 25kg Cargo aircraft: 100kg
14.5. Environmental hazards Environment Marine pollutant	NONE NO
14.6. Special precautions for user	The goods should be transported in the original packaging and in any case in packagings made of material resistant to their content and not likely to generate reactions.
14.7.Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable



#### **SECTION 15: Other Regulatory Information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC, (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1272/2008 (CLP)

15.2. Chemical Safety Assessment Information N/A.

### **SECTION 16: Other Information**

- Customs Tariff Number 84241000

- HS CODE # 292990

Main bibliographic sources:

- ECDIN Environmental Chemicals Data and Information Network Joint Research Centre, Commission of the European Communities
- Analysis and test report by the Polytechnic of Turin, Science of Material & Chemical Engineering Department

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATL: Atmospheric Life Time

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging. Regulation No. 1272/2008.

DCDA: Dicyandiamide

DSD: Directive 67/548/EEC.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

GWP: Global Warming Potential

HS Code: Harmonized System Code

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

N/A.: Not available

**ODP: Ozone Depletion Potential** 

PBT: Persistent bio accumulative and Toxic

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent and very bio accumulative

Comply with Manufacturer's installation and maintenance procedures

EUH210: Safety data sheet available on request.



Validated and verified by	Mr. Enzo Perna, Quality Mgr.
Revision #5	February 1, 2018

### WARRANTY

All fire suppressant products carry a 3 year warranty after date of shipment against defects in materials and workmanship under conditions of normal use. Any product found defective within this period shall be replaced or repaired at ESP INTERNATIONAL SRL discretion.

Manufacturer's warranty, terms and conditions apply in all cases. No other warranty express or implied is valid.

Manufacturer shall not be liable or responsible, however, for any defects attributed to normal wear and tear, erosion or corrosion or improper storage, use or maintenance, negligence. In addition, Manufacturer shall not be liable for any defects arising from alteration or modification, nor from consequential incidental damages. Buyer shall give Manufacturer an opportunity to investigate. Transportation charges for the return of fire suppressants to Manufacturer shall be prepaid by Buyer.

<u>Notice to reader</u>: information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law and regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.